

ACCESS CONTROL FOR THE FARMS

Control of Biosecurity

ACSCON plus Monitor Device to manage the access control

- It connects up to 2 units of TCA identification terminals.
- It communicates via 2G, 3G, 4G or with local WIFI.
- It is possible to add a lithium battery.
- It informs about the geolocation of the TCA units.

TECHNICAL SPECIFICATIONS

| | |
|---------------|--|
| REFERENCE | ACSCON plus |
| INPUTS | 2 Digital inputs |
| OUTPUTS | 2 Relays 1 BUS port WIFI IEEE 802.11 b/g/n Modem with communications: 2G, 3G y 4G Global |
| VOLTAGE | 100 - 240 Vac |
| MEASURES | 240x191x110 mm |
| IP PROTECTION | IP67 |
| NORMATIVES | 89/392/EEC - 73/336/EEC - 73/23/EEC |



TCA Terminal to identify the users and visitors

- Device for the access control with capacitive keyboard.
- It can monitor up to 200 users.
- It allows to update new users and visitors.
- It easily identifies the users and visitors by:



TECHNICAL SPECIFICATIONS

| | |
|---------------|-------------------------------------|
| REFERENCE | TCA |
| MEASURES | 160x80x40mm |
| IP PROTECTION | IP67 |
| NORMATIVES | 89/392/EEC - 73/336/EEC - 73/23/EEC |

