

SILOWS

Device to manage and weigh silos

The SILOWS computers are digital devices to monitor the silos:

SILOWS 1 to monitor 1 silo.

SILOWS 3 to monitor up to 3 silos.

SILOWS Advanced computer for silo weight management

FUNCTIONS

- It provides useful statistics of feed consumption and it monitors the weight of the silo.
- It has an alarm for level of weigh and for empty silo.
- It automatically detects and records the loading of the silo.
- The dosage of feed can be programed with 14 different points.
- It is possible to connect a temperature sensor to monitor the room temperature or the silo temperature.
- Surveillance system for water and feed consumption.
- It has 3 independent clocks with 6 programs for each of one.
- Input for water counter and 2 counters free configurables for electricity, medicines, etc.
- 4 relays.
- Sequential system for the opening of the silos.
- Automatic detection of wrong functioning of the load cells to avoid erroneous weighs.
- Power supply at AC from 100 to 240Vac. It also has an input of 12VDC for connection to power supply of photovoltaic systems.

COMMUNICATIONS

- Once is connected to the central communication box CT2, then the SILOWS can be monitored online with the website and mobile app CTIportal. From your mobile, pc or tablet you can have full remote control of the Silows computers for silos:
 - Statistics of weighs, loadings, feed and water consumption, temperature, etc
 - Remote programming and maintenance of equipment.
 - Unified control and management of all silos in the system.



TECHNICAL SPECIFICATIONS

REFERENCE	SILOWS 1 - Equipment to weigh 1 silo SILOWS 3 - Equipment to weigh 3 silos
INPUTS	3 Digital inputs SILOWS 1: 1 Input for junction box (1 silo) SILOWS 3: 3 Inputs for junction box (3 silos)
OUTPUTS	4 Relays 1 Communications port CAN
VOLTAGE	100Vac - 240Vac / 12Vdc
MEASURES	200x170x90 mm
IP PROTECTION	IP67
NORMATIVES	89/392/CEE - 73/336/CEE - 73/23/CEE

